

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Octane Booster MAX

UFI: AT4Y-Y8HT-P00S-DDEF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

octane number improver

Fuel additive

1.3. Details of the supplier of the safety data sheet

Company name:	GAT Gesellschaft für Kraftstoff- und Automobiltechnologie mbH		
Street:	Alt Saale 2		
Telephone:	+49 (0)3672-48 38 0-66	Telefax:	+49 (0)3672-48 38 0-22
E-mail:	info@gat-international.de		
Contact person:	Research & Development	Telephone:	+49 (0)3672-48 38 0-66
E-mail:	info@gat-international.de		
Internet:	www.gat-international.de		
Responsible Department:	Research & Development		

1.4. Emergency telephone number: for Germany: +49-361-730730

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226
Acute Tox. 3; H331
Acute Tox. 3; H301
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335
STOT RE 2; H373
Asp. Tox. 1; H304
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

xylene
ethylbenzene
Methylcyclopentadienyl manganese tricarbonyl
Solvent naphtha (petroleum), heavy arom.

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 2 of 13

H301+H331	Toxic if swallowed or if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310	Immediately call a POISON CENTER/doctor.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P233	Keep container tightly closed.
P403	Store in a well-ventilated place.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 3 of 13

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1330-20-7	xylene			60 - < 80 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
100-41-4	ethylbenzene			10 - < 20 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
12108-13-3	Methylcyclopentadienyl manganese tricarbonyl			1 - < 10 %
	235-166-5		01-2119495971-23	
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 3, Skin Irrit. 2, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H315 H372 H400 H410			
64742-94-5	Solvent naphtha (petroleum), heavy arom.			1 - < 10 %
	919-284-0	649-424-00-3	01-2119463588-24	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411 EUH066			
91-20-3	naphthalene			0.1 - < 1 %
	202-049-5	601-052-00-2		
	Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H351 H302 H400 H410			
108-31-6	maleic anhydride			< 0.001 %
	203-571-6	607-096-00-9		
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1A, STOT RE 1; H302 H314 H318 H334 H317 H372 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	60 - < 80 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
100-41-4	202-849-4	ethylbenzene	10 - < 20 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)	
12108-13-3	235-166-5	Methylcyclopentadienyl manganese tricarbonyl	1 - < 10 %
		inhalation: LC50 = 0,247 mg/l (vapours); inhalation: ATE = 0,005 mg/l (dusts or mists); dermal: LD50 = 196,7 mg/kg; oral: LD50 = 58 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
91-20-3	202-049-5	naphthalene	0.1 - < 1 %
		oral: ATE = 500 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
108-31-6	203-571-6	maleic anhydride	< 0.001 %
		dermal: LD50 = 2620 mg/kg; oral: LD50 = 400 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 4 of 13

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Call a physician immediately. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Call a physician immediately.

Remove person to fresh air and keep comfortable for breathing.

If swallowed, rinse mouth with water (only if the person is conscious).

If unconscious but breathing normally, place in recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. Headache, Nausea

Ingestion causes nausea, weakness and central nervous system effects. Adverse human health effects and symptoms: depression of central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder. In case of fire, use sand, extinguishing powder or alcohol resistant foam. carbon dioxide (CO₂)

Unsuitable extinguishing media

Water. Full water jet

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Hazardous decomposition products: Carbon dioxide, Carbon monoxide, Metal oxide smoke, toxic

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 5 of 13

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

octane number improver

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 6 of 13

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
100-41-4	Ethylbenzene	100	442		TWA (8 h)	
		200	884		STEL (15 min)	
91-20-3	Naphtalene	10	50		TWA (8 h)	
1330-20-7	Xylene, mixed isomers, pure	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: yellow /orange - dark brown
Odour: characteristic

Test method

Melting point/freezing point: not determined
Boiling point or initial boiling point and boiling range: >136 °C
Lower explosion limits: 0,6 vol. %
Upper explosion limits: 7 vol. %
Flash point: 31 °C DIN EN ISO 3679
Auto-ignition temperature: 460 °C
Decomposition temperature: not determined
pH-Value: not applicable
Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 7 of 13

Solubility in other solvents

miscible with most organic solvents

Dissolution rate:

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

8 hPa

(at 20 °C)

Density:0,89 g/cm³**Relative density:**

not determined

Relative vapour density:

not determined

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics**Evaporation rate:**

not determined

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

UV-radiation/sunlight

10.5. Incompatible materials

Acid, concentrated;

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Toxic if inhaled.

Toxic if swallowed.

ATEmix calculated

ATE (oral) 1169 mg/kg; ATE (dermal) 1137 mg/kg; ATE (inhalation vapour) 2,070 mg/l; ATE (inhalation dust/mist) 0,0950 mg/l

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
12108-13-3	Methylcyclopentadienyl manganese tricarbonyl				
	oral	LD50 58 mg/kg	Rat		
	dermal	LD50 196,7 mg/kg	Rabbit		
	inhalation vapour	LC50 0,247 mg/l	Rat		
	inhalation dust/mist	ATE 0,005 mg/l			
91-20-3	naphthalene				
	oral	ATE 500 mg/kg			
108-31-6	maleic anhydride				
	oral	LD50 400 mg/kg	Rat	GESTIS	
	dermal	LD50 2620 mg/kg	Rabbit	GESTIS	

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene; ethylbenzene;

Methylcyclopentadienyl manganese tricarbonyl)

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 9 of 13

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-31-6	maleic anhydride					
	Acute algae toxicity	ErC50	29 mg/l	72 h	Desmodesmus subspicatus	IUCLID

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 1307

14.2. UN proper shipping name:

XYLENES

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

30

Tunnel restriction code:

D/E

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 10 of 13

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: P
Special Provisions: 223
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Methylcyclopentadienyl manganese tricarbonyl

14.6. Special precautions for user

Warning: Combustible liquid.

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 11 of 13

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

H2 ACUTE TOXIC

Additional information:

P5c, E2

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

3 - highly hazardous to water

Additional information

Contains: >30% aromatic hydrocarbons

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,9,11,12,14.

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 12 of 13

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Flam. Liq. 3: Flammable liquids, hazard category 3
Acute Tox. 1: Acute toxicity, hazard category 1
Acute Tox. 2: Acute toxicity, hazard category 2
Acute Tox. 3: Acute toxicity, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Resp. Sens. 1: Respiratory sensitisation, hazard category 1
Skin Sens. 1A: Skin sensitisation, hazard category 1A
Carc. 2: Carcinogenicity, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container

Octane Booster MAX

Revision: 03.12.2025

Product code: 100435

Page 13 of 13

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 3; H331	
Acute Tox. 3; H301	
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H301+H331	Toxic if swallowed or if inhaled.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)