

Technical Data Sheet



Reaction time
works during operation



Application field
for use in all gasoline engines



Consumption
100 ml per 15 L



Application interval
with every tank filling

Octane Booster MAX

Application

Add with every filling. Sufficient for 45 L petrol. For larger capacities add 100 ml per 15 L of fuel.

Description

AUTOSCHLÜSSEL Octane Booster MAX to increase the octane number of low octane fuels or for use in engines with higher octane requirements.

Advantages

Protects valve seats while running on unleaded fuel. Improves start and full-load performance. Provides smoother idling. Prevents deposits on valves and in the combustion chamber. Increases the octane number by 3 up to 8 points. Improved engine performance and operational reliability. Protects valve seat from excessive wear. Ensures stable combustion process and an improved CO-value.

Packing sizes	Packing unit	Article number
300 ml	24 x 300 ml	Art. 09683
other sizes available on request		

Properties

Physical state	liquid
Color	yellow/orange - brown
Density (15 °C)	0,89 g/cm ³
Flash point	31 °C

Compatibility

Recommended for all gasoline engines.

Safety instructions

Follow the application instructions in the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Keep out of reach of children. If medical advice is needed, have product container or label at hand and call a poison centre/doctor.

Disposal

Dispose of this product and container according to national/regional regulations.