

Technical Data Sheet



Reaction time
works during operation



Application field
for use in all gasoline engines



Consumption
50 ml per 10 L



Application interval
with every tank filling

Fuel System Cleaner PLUS

Application

Recommended to add to the petrol tank before every refueling. Sufficient for 40-60 liters of petrol. For larger capacities add 50 ml per 10 liter fuel. Product works during the operation.

Description

AUTOSCHLÜSSEL Fuel System Cleaner PLUS is suitable for use in all petrol engines, generators and high-performance engines (e.g. boat, bike etc.). Solves operationally caused contamination in the entire fuel system from the tank to the combustion chamber. Dissolves resinifications and gums in the carburetor and injection system. Removes coking and unburned carbon residues in the upper cylinder area. Reliably binds moisture from the fuel and prevents condensation to prevent failure.

Advantages

Clean and powerful combustion process and highly efficient engine running. The product has a positive impact on fuel consumption, improved engine performance and reduced exhaust gas emissions. Protects against corrosion, which increases the life of injectors and fuel pumps. Has a positive effect for the lifetime of the catalyst.

Packing sizes	Packing Unit	Article Number
100 ml	24 x 100 ml	
300 ml	24 x 300 ml	Art. 09684
1 L	12 x 1 L	
5 L	-	

other sizes available on request

Properties

Physical state	liquid
Color	red
Density (15 °C)	0,82 g/cm ³ DIN 12185
Flash point	-9 °C ISO 3679
Viscosity (40 °C)	0,73 mm ² /s DIN EN ISO 3104

Compatibility

Recommended for all gasoline engines.

Safety instructions

Follow the application instructions in the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Keep out of reach of children. If medical advice is needed, have product container or label at hand and call a poison centre/doctor.

Disposal

Dispose of this product and container according to national/regional regulations.

